TEREX DIESEL

LIGHT TOWER · 50 Hz

TRX LT P 33

33 kVA Light Tower with Perkins Engine

4 × 200 W
LED lighting

7.5 m
Mast height

33 kVA
Standby power

115 L
Fuel tank

LIGHTING

Lamp type		LED
Number of lamps		4
Lamp power	W	200
Total lamp power	W	800
Mast height	m	7.5
Mast lifting system		Mechanical / electric motor

GENERATOR

Standby power	kVA	33
Prime power	kVA	26.4
Frequency	Hz	50
Speed	rpm	1500
Voltage	V	230/400
Fuel		Diesel

DIMENSIONS AND WEIGHT

		Transport	Working
Width A / A1	mm	1700	2800
Length B / B1	mm	2180	3000
Height C / C1	mm	2340	7500
Weight	kg		1250
Fuel tank	L		115

TEREX DIESEL
www.terexdiesel.com
Deri OSB District, Tanen Street, Deri OSB Site No. 8, Tuzla, Istanbul
info@terexdiesel.com +90 216 634 34 06

TEREX DIESEL

LIGHT TOWER · 50 Hz

TRX LT P 33

ENGINE

Make		Perkins
Model		1103A-33G
Fuel		Diesel
Fuel injection		Direct injection
Aspiration		Naturally aspirated
Number of cylinders		3
Bore × stroke	mm	105 × 127
Displacement	L	3.31
Cooling		Water-cooled
Speed	rpm	1500
Governor		Mechanical
Oil capacity	L	8.3
Coolant capacity	L	10.2

ALTERNATOR

Make		TEREX
Model		TA180-24N2
Voltage	V	230/400
Frequency	Hz	50
Protection / insulation class		IP23/H
Winding pitch		2/3
Excitation		Self-excited
AVR model		SX460

Technical data may change without notice due to product development. Image is representative.

TEREX DIESEL

www.terexdiesel.com

Deri OSB District, Tanen Street, Deri OSB Site No. 8, Tuzla, Istanbul

info@terexdiesel.com +90 216 634 34 06